Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 197368

FAIRCHILD SEMICONDUCTOR™

November 1983
Revised August 2000

CD4051BC • CD4052BC • CD4053BC
Single 8-Channel Analog Multiplexer/Demultiplexer • Dual 4-Channel Analog Multiplexer/Demultiplexer • Triple 2-Channel Analog Multiplexer/Demultiplexer

CD4051BC • CD4052BC • CD4053BC Single 8-Channel Analog Multiplexer/Demultiplexer • Dual 4-Channel Analog Multiplexer/Demultiplexer • Triple 2-Channel Analog Multiplexer/Demultiplexer

General Description

The CD4051BC, CD4052BC, and CD4053BC analog multiplexers/demultiplexers are digitally controlled analog switches having low "ON" impedance and very low "OFF" leakage currents. Control of analog signals up to $15V_{p-p}$ can be achieved by digital signal amplitudes of 3–15V. For example, if V_{DD} = 5V, V_{SS} = 0V and V_{EE} = –5V, analog signals from –5V to +5V can be controlled by digital inputs of 0–5V. The multiplexer circuits dissipate extremely low quiescent power over the full V_{DD}–V_{SS} and V_{DD}–V_{EE} supply voltage ranges, independent of the logic state of the control signals. When a logical "1" is present at the inhibit input terminal all channels are "OFF".

CD4051BC is a single 8-channel multiplexer having three binary control inputs. A, B, and C, and an inhibit input. The three binary signals select 1 of 8 channels to be turned "ON" and connect the input to the output.

CD4052BC is a differential 4-channel multiplexer having two binary control inputs, A and B, and an inhibit input. The two binary input signals select 1 or 4 pairs of channels to be turned on and connect the differential analog inputs to the differential outputs.

CD4053BC is a triple 2-channel multiplexer having three separate digital control inputs, A, B, and C, and an inhibit input. Each control input selects one of a pair of channels which are connected in a single-pole double-throw configuration.

Features

- Wide range of digital and analog signal levels: digital 3 – 15V, analog to $15V_{p-p}$
- Low "ON" resistance: 80Ω (typ.) over entire $15V_{p-p}$ signal-input range for $V_{DD} - V_{EE}$ = 15V
- High "OFF" resistance: channel leakage of ±10 pA (typ.) at $V_{DD} - V_{EE}$ = 10V
- Logic level conversion for digital addressing signals of 3 – 15V ($V_{DD} - V_{SS}$ = 3 – 15V) to switch analog signals to 15 V_{p-p} ($V_{DD} - V_{EE}$ = 15V)
- Matched switch characteristics: ΔR_{ON} = 5Ω (typ.) for $V_{DD} - V_{EE}$ = 15V
- Very low quiescent power dissipation under all digital-control input and supply conditions: 1 μ W (typ.) at $V_{DD} - V_{SS} = V_{DD} - V_{EE}$ = 10V
- Binary address decoding on chip

Ordering Code:

Order Number	Package Number	Package Description
CD4051BCM	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow
CD4051BCSJ	M16D	16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
CD4051BCMTC	MTC16	16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
CD4051BCN	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide
CD4052BCM	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow
CD4052BCSJ	M16D	16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
CD4052BCN	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide
CD4053BCM	M16A	16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow
CD4053BCSJ	M16D	16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
CD4053BCN	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

© 2000 Fairchild Semiconductor Corporation

Connection Diagrams

Pin Assignments for DIP and SOIC

CD4051BC



TOP VIEW

CD4052BC



TOP VIEW

CD4053BC



TOP VIEW

Truth Table

INPUT STATES				"ON" CHANNELS		
INHIBIT	**C**	**B**	**A**	**CD4051B**	**CD4052B**	**CD4053B**
0	0	0	0	0	0X, 0Y	cx, bx, ax
0	0	0	1	1	1X, 1Y	cx, bx, ay
0	0	1	0	2	2X, 2Y	cx, by, ax
0	0	1	1	3	3X, 3Y	cx, by, ay
0	1	0	0	4		cy, bx, ax
0	1	0	1	5		cy, bx, ay
0	1	1	0	6		cy, by, ax
0	1	1	1	7		cy, by, ay
1	*	*	*	NONE	NONE	NONE

*Don't Care condition.

Logic Diagrams

CD4051BC



CD4052BC



Logic Diagrams (Continued)

CD4053BC



Absolute Maximum Ratings (Note 1)

DC Supply Voltage (V_{DD})	−0.5 V_{DC} to +18 V_{DC}
Input Voltage (V_{IN})	−0.5 V_{DC} to V_{DD} +0.5 V_{DC}
Storage Temperature Range (T_S)	−65°C to +150°C
Power Dissipation (P_D)	
Dual-In-Line	700 mW
Small Outline	500 mW
Lead Temperature (T_L) (soldering, 10 seconds)	260°C

Recommended Operating Conditions

DC Supply Voltage (V_{DD})	+5 V_{DC} to +15 V_{DC}
Input Voltage (V_{IN})	0V to V_{DD} V_{DC}
Operating Temperature Range (T_A)	
CD4051BC/CD4052BC/CD4053BC	−40°C to +85°C

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The Electrical Characteristics tables provide conditions for actual device operation.

DC Electrical Characteristics (Note 2)

Symbol	Parameter	Conditions		−40°C		+25°			+85°C		Units
				Min	Max	Min	Typ	Max	Min	Max	
Control A, B, C and Inhibit											
I_{IN}	Input Current	V_{DD} = 15V, V_{EE} = 0V V_{IN} = 0V			−0.1		-10^{-5}	−0.1		−1.0	µA
		V_{DD} = 15V, V_{EE} = 0V V_{IN} = 15V			0.1		10^{-5}	0.1		1.0	µA
I_{DD}	Quiescent Device Current	V_{DD} = 5V			20			20		150	µA
		V_{DD} = 10V			40			40		300	µA
		V_{DD} = 15V			80			80		600	µA
Signal Inputs (V_{IS}) and Outputs (V_{OS})											
R_{ON}	"ON" Resistance (Peak for $V_{EE} \le V_{IS} \le V_{DD}$)	R_L = 10 kΩ (any channel selected)	V_{DD} = 2.5V, V_{EE} = −2.5V or V_{DD} = 5V, V_{EE} = 0V		850		270	1050		1200	Ω
			V_{DD} = 5V, V_{EE} = −5V or V_{DD} = 10V, V_{EE} = 0V		330		120	400		520	Ω
			V_{DD} = 7.5V, V_{EE} = −7.5V or V_{DD} = 15V, V_{EE} = 0V		210		80	240		300	Ω
ΔR_{ON}	Δ "ON" Resistance Between Any Two Channels	R_L = 10 kΩ (any channel selected)	V_{DD} = 2.5V, V_{EE} = −2.5V or V_{DD} = 5V, V_{EE} = 0V				10				Ω
			V_{DD} = 5V V_{EE} = −5V or V_{DD} = 10V, V_{EE} = 0V				10				Ω
			V_{DD} = 7.5V, V_{EE} = −7.5V or V_{DD} = 15V, V_{EE} = 0V				5				Ω
	"OFF" Channel Leakage Current, any channel "OFF"	V_{DD}=7.5V, V_{EE}=−7.5V O/I=±7.5V, I/O=0V			±50		±0.01	±50		±500	nA
	"OFF" Channel Leakage Current, all channels "OFF" (Common OUT/IN)	Inhibit = 7.5V V_{DD} = 7.5V, V_{EE} = −7.5V, O/I = 0V	CD4051		±200		±0.08	±200		±2000	nA
			D4052		±200		±0.04	±200		±2000	nA
		I/O = ±7.5V	CD4053		±200		±0.02	±200		±2000	nA
Control Inputs A, B, C and Inhibit											

DC Electrical Characteristics (Continued)

Symbol	Parameter	Conditions	−40°C		+25°			+85°C		Units
			Min	Max	Min	Typ	Max	Min	Max	
V_{IL}	LOW Level Input Voltage	$V_{EE} = V_{SS}$ R_L = 1 kΩ to V_{SS}								
		I_{IS}<2 μA on all OFF Channels								
		$V_{IS} = V_{DD}$ thru 1 kΩ								
		V_{DD} = 5V		1.5			1.5		1.5	V
		V_{DD} = 10V		3.0			3.0		3.0	V
		V_{DD} = 15V		4.0			4.0		4.0	V
V_{IH}	HIGH Level Input Voltage	V_{DD} = 5	3.5		3.5			3.5		V
		V_{DD} = 10	7		7			7		V
		V_{DD} = 15	11		11			11		V
I_{IN}	Input Current	V_{DD} = 15V, V_{EE} = 0V		−0.1		-10^{-5}	−0.1		−1.0	μA
		V_{IN} = 0V								
		V_{DD} = 15V, V_{EE} = 0V		0.1		10^{-5}	0.1		1.0	μA
		V_{IN} = 15V								

Note 2: All voltages measured with respect to V_{SS} unless otherwise specified.

AC Electrical Characteristics (Note 3)

$T_A = 25°C$, $t_r = t_f = 20$ ns, unless otherwise specified.

Symbol	Parameter	Conditions	V_{DD}	Min	Typ	Max	Units
t_{PZH},	Propagation Delay Time from	$V_{EE} = V_{SS} = 0V$	5V		600	1200	ns
t_{PZL}	Inhibit to Signal Output	$R_L = 1\ k\Omega$	10V		225	450	ns
	(channel turning on)	$C_L = 50$ pF	15V		160	320	ns
t_{PHZ},	Propagation Delay Time from	$V_{EE} = V_{SS} = 0V$	5V		210	420	ns
t_{PLZ}	Inhibit to Signal Output	$R_L = 1\ k\Omega$	10V		100	200	ns
	(channel turning off)	$C_L = 50$ pF	15V		75	150	ns
C_{IN}	Input Capacitance						
	Control input				5	7.5	pF
	Signal Input (IN/OUT)				10	15	pF
C_{OUT}	Output Capacitance						
	(common OUT/IN)						
	CD4051		10V		30		pF
	CD4052	$V_{EE} = V_{SS} = 0V$	10V		15		pF
	CD4053		10V		8		pF
C_{IOS}	Feedthrough Capacitance				0.2		pF
C_{PD}	Power Dissipation Capacitance						
	CD4051				110		pF
	CD4052				140		pF
	CD4053				70		pF
Signal Inputs (V_{IS}) and Outputs (V_{OS})							
	Sine Wave Response	$R_L = 10\ k\Omega$					
	(Distortion)	$f_{IS} = 1$ kHz	10V		0.04		%
		$V_{IS} = 5\ V_{p-p}$					
		$V_{EE} = V_{SI} = 0V$					
	Frequency Response, Channel	$R_L = 1\ k\Omega$, $V_{EE} = 0V$, $V_{IS} = 5V_{p-p}$,	10V		40		MHz
	"ON" (Sine Wave Input)	$20 \log_{10} V_{OS}/V_{IS} = -3$ dB					
	Feedthrough, Channel "OFF"	$R_L = 1\ k\Omega$, $V_{EE} = V_{SS} = 0V$, $V_{IS} = 5V_{p-p}$,	10V		10		MHz
		$20 \log_{10} V_{OS}/V_{IS} = -40$ dB					
	Crosstalk Between Any Two	$R_L = 1\ k\Omega$, $V_{EE} = V_{SS} = 0V$, $V_{IS}(A) = 5V_{p-p}$	10V		3		MHz
	Channels (frequency at 40 dB)	$20 \log_{10} V_{OS}(B)/V_{IS}(A) = -40$ dB (Note 4)					
t_{PHL}	Propagation Delay Signal	$V_{EE} = V_{SS} = 0V$	5V		25	55	ns
t_{PLH}	Input to Signal Output	$C_L = 50$ pF	10V		15	35	ns
			15V		10	25	ns
Control Inputs, A, B, C and Inhibit							
	Control Input to Signal	$V_{EE} = V_{SS} = 0V$, $R_L = 10\ k\Omega$ at both ends					
	Crosstalk	of channel.	10V		65		mV (peak)
		Input Square Wave Amplitude = 10V					
t_{PHL},	Propagation Delay Time from	$V_{EE} = V_{SS} = 0V$	5V		500	1000	ns
t_{PLH}	Address to Signal Output	$C_L = 50$ pF	10V		180	360	ns
	(channels "ON" or "OFF")		15V		120	240	ns

Note 3: AC Parameters are guaranteed by DC correlated testing.

Note 4: A, B are two arbitrary channels with A turned "ON" and B "OFF".

Special Considerations

In certain applications the external load-resistor current may include both V_{DD} and signal-line components. To avoid drawing V_{DD} current when switch current flows into IN/OUT pin, the voltage drop across the bidirectional switch must not exceed 0.6V at $T_A \leq 25°C$, or 0.4V at $T_A > 25°C$ (calculated from R_{ON} values shown). No V_{DD} current will flow through R_L if the switch current flows into OUT/IN pin.

Typical Performance Characteristics

"ON" Resistance vs Signal Voltage for $T_A = 25°C$



"ON" Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 10V$



"ON" Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 15V$



"ON" Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 5V$



Switching Time Waveforms



SIGNAL INPUT TO SIGNAL OUTPUT



ADDRESS TO SIGNAL OUTPUT









Physical Dimensions inches (millimeters) unless otherwise noted



16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow
Package Number M16A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



NOTES:

A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.

B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M16DRevB1

16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
Package Number M16D

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC16

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide
Package Number N16E

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com